


MT SERIES

SYNTEC

The outstanding designed mechanism established by years experienced engineering experts
Insist on using **NSK** top-level ball screw linear guides and high-precision spindle bearings
The brand new version cooperates with Taiwanese well-known controller **SYNTEC**


New Style / Best Selection / More Functionalities




 YouTube



 Find us on
Facebook








 KEEN CHIEF
www.keenchief.com


SPECIFICATION

Model Type	MT52	MT52-PLUS	MT36	MT36-PLUS
Maximum swing	200mm		200mm	
Spindle center to sub table	42mm		42mm	
Hole trough spindle	52mm		42mm	
Bar hole capacity	42mm		27mm	
Spindle nose	ASA-5(6")		ASA-4(5")	
Spindle motor	5.5/7.5KW		5.5/7.5KW	
Table X-axis travel	300mm Φ 600mm	400mm Φ 800mm	300mm Φ 600mm	400mm Φ 800mm
Table Z-axis travel	200mm		200mm	
Rapid traverse rate X-axis	12M/MIN		12M/MIN	
Rapid traverse rate Z-axis	12M/MIN		12M/MIN	
Total power required	AC3 Φ 220V/60HZ 6KVA		AC3 Φ 220V/60HZ 6KVA	
Machine weight	1600KG		1550KG	
Machine layout (mm) WxDxH	2120x1300x1900		2120x1300x1900	
Standard Accessories	6" (150mm) CHUCK		5" (125mm) CHUCK	
	Spindle with C axis Hydraulically (power) system unit Foot switch for chucking Coolant system LED Working light/Caution light Tool box		Automatic lubrication unit OD tool holder 2pcs ID tool holder 4pcs (20 Φ) Chip Conveyor External safety operation switch (panel) Transformer	
Optional Accessories	LNS Barfeeder interface Robot Parts Loader Interface Boring bar holder 4pcs Door interlock Oil clean system Chip container		Collect Chucks 16C or 42CR Spindle Break Parts Catcher Automatic Door	


Please refer to each controller provider for their standard and optional features



FANUC



SYNTEC



FAGOR

! The controller model will be changed depending on the version or year provided by the controller provider. For more details, please contact or email us.